

## TEST DATA

**Test Data No. :** \_\_\_\_\_  
 Station : \_\_\_\_\_  
 Protected Eqpt. ID : \_\_\_\_\_  
 Date of Test : \_\_\_\_\_  
 CT Ratio HV/Connection : \_\_\_\_\_  
 CT Ratio MV/Connection : \_\_\_\_\_  
 CT Ratio LV/Connection : \_\_\_\_\_  
 CT Ratio LV/Connection : \_\_\_\_\_  
 Breakers Tripped : \_\_\_\_\_

***Relay Specifications:***

Brand: \_\_\_\_\_  
 Model: \_\_\_\_\_  
 Serial No. \_\_\_\_\_  
 Voltage Rating: \_\_\_\_\_  
 Current Rating: \_\_\_\_\_  
 Serial No. \_\_\_\_\_  
 Manufacturing Date: \_\_\_\_\_

**A. TRANSFORMER DATA**

WINDING	W1 (HV)	W2 (LV)	W3 (TV)
POWER RATING, MVA			
VOLTAGE RATING			
WINDING CONNECTION			

**B. RELAY SETTINGS**

PARAMETERS	SET VALUE
TAP 1 (WINDING 1)	
TAP 2 (WINDING 2)	
OPERATING PICK-UP	
UNRESTRAINED PICK-UP	
BASE POINT 1	
BASE POINT 2	
BASE POINT 3	
SLOPE 1	
SLOPE 2	
SLOPE 3	

# TRANSFORMER DIFFERENTIAL RELAY TEST DATA

Page

2 of 3

## C. PICK-UP TEST

WDG	Type of Test	PHASE A	PHASE B	PHASE C	3 PHASE
1-CT1	Pick-up				
	Drop-out				
1-CT2	Pick-up				
	Drop-out				
2-CT1	Pick-up				
	Drop-out				
2-CT2	Pick-up				
	Drop-out				
3-CT1	Pick-up				
	Drop-out				
3-CT2	Pick-up				
	Drop-out				
RELAY TARGET/INDICATION					

## D. TIME TEST

WDG	MULTIPLES $I_{DIFF}$	PHASE A		PHASE B		PHASE C	
		AMP	SEC	AMP	SEC	AMP	SEC
1	$I_{DIFF} > @ \_\_ x I_{pick-up}$						
2	$I_{DIFF} > @ \_\_ x I_{pick-up}$						
3	$I_{DIFF} > @ \_\_ x I_{pick-up}$						

## E. SLOPE/CHARACTERISTIC TEST

Test No.	CT1 HVS (A)	CT1MVS (A)	$I_d$ pu	$I_{res}$ pu	Remarks
1	$I_A =$ $I_B =$ $I_C =$	$I_A =$ $I_B =$ $I_C =$			
2	$I_A =$ $I_B =$ $I_C =$	$I_A =$ $I_B =$ $I_C =$			
3	$I_A =$ $I_B =$ $I_C =$	$I_A =$ $I_B =$ $I_C =$			
4	$I_A =$ $I_B =$ $I_C =$	$I_A =$ $I_B =$ $I_C =$			
5	$I_A =$ $I_B =$ $I_C =$	$I_A =$ $I_B =$ $I_C =$			
6	$I_A =$ $I_B =$ $I_C =$	$I_A =$ $I_B =$ $I_C =$			
COMPUTED M1 =					
COMPUTED M2 =					

## F. STABILITY TEST

% FULL LOAD	CURRENT		PHASE A			PHASE B			PHASE C		
	W1	W2	$I_{RES}$	$I_{DIFF}$	TRIP	$I_{RES}$	$I_{DIFF}$	TRIP	$I_{RES}$	$I_{DIFF}$	TRIP
100%											

REMARKS: \_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

## G. GROUND OVERCURRENT SETTING

## 1. MINIMUM PICK-UP

PARAMETERS	PHASE A	PHASE B	PHASE C	GROUND
LOW SET CURRENT PICK-UP (A)				
LOW SET CURRENT DROP OUT (A)				
RELAY INDICATION/TARGET				
HIGH SET CURRENT PICK-UP (A)				
HIGH SET TIME (ms)				
RELAY INDICATION/TARGET				

## 2. TIME-ELEMENT OPERATING TIME CHARACTERISTIC

MULTIPLES OF TAP VALUE	A		B		C		MULTIPLES OF TAP VALUE	GROUND	
	AMP	SEC	AMP	SEC	AMP	SEC		AMP	SEC
% Set Tap									
% Set Tap									
% Set Tap									
% Set Tap									
% Set Tap									
% Set Tap									
% Set Tap									
% Set Tap									
% Set Tap									

## H. FUNCTIONAL TESTING / SIMULATION

FUNCTION	CONTROLLING BREAKERS	SIMULATION USED		BREAKERS TRIPPED	REMARKS
		INJECTION	SIGNALLING		

Tested by :

Concurred by :

\_\_\_\_\_  
Contractor - Test Engineer\_\_\_\_\_  
Owner's Representative

TEST INSTRUMENTS: \_\_\_\_\_

(Eqpt.ID/Make/Model/SN/  
Date of last calibration)  
\_\_\_\_\_  
\_\_\_\_\_